



Plattierte Flansche und Stutzen PN 6 bis PN 40 mit glatter Dichtleiste sowie Nut und Feder

Werknorm
PF 6 - 40

Maße in mm

In Anlehnung an DIN 28025

Nenn- druck PN	Nenn- weite DN	d1		Flansch				Plattierung							Schrauben		Gew. kg	
		Reihe 1	Reihe 2	D	b	k	h	L	≈d4	s	s1	f	f1	f2	An- zahl	d2		
25	200	219,1	–	360	32	310	80	ca. 500	278	5,0	5,0	4	10	10	12	26	19,0	
	250	273,0	267,0	425	37	370	88		335							30	29,0	
	300	323,9	318,0	485	44	430	92		395							16	33	57,0
	350	355,6	368,0	555	48	490	100		450							36	75,0	
	400	406,4	419,0	620	54	550	110		505	20	36				93,0			
	450	457,0	470,0	670	59	600	125		555		39				111,0			
	500	508,0	521,0	730	63	660	125		615	39	173,0							
	600	609,6	622,0	845	74	770	130		720	8,0	8,0							
40	25	33,7	30,0	115	18	85	40	ca. 500	68	3,6	2,6	3	10	10	4	14	1,5	
	32	42,4	38,0	140	18	100	42		78							18	2,1	
	40	48,3	44,5	150	18	110	45		88							18	2,4	
	50	60,3	57,0	165	20	125	48		102							2,9	3,1	
	65	76,1	–	185	20	145	52		122	8	3,9							
	80	88,9	–	200	22	160	58		138		5,1							
	100	114,3	108,0	235	25	190	65		162	4,0	3,6							
	125	139,7	133,0	270	27	220	68		188		26				7,5			
	150	168,3	159,0	300	31	250	75		218	4	4,0							
	200	219,1	–	375	42	320	88		285		12	30	26,5					
	250	273,0	267,0	450	50	385	105		345	5,0	5,0	33	42,0					
	300	323,9	318,0	515	58	450	115		410	6,0	6,0	16	36	60,0				
	350	355,6	368,0	580	65	510	125		465	8,0	8,0		36	87,0				
	400	406,4	419,0	660	75	585	135		535	10,0	10,0	20	39	131,0				
	450	457,0	470,0	685	78	610	135		560				42	133,0				
	500	508,0	521,0	755	80	670	140		615					42	165,0			

Die vorgegebene Rohrwanddicke s ist Regelausführung. Ab DN 200 auch dickere Ausführung möglich.



Erich Pokrandt GmbH
August-Bebel-Str. 3
67454 Hassloch / Pfalz

Telefon: 06324 / 923 923
Telefax: 06324 / 923 999
e-mail: info@pokrandt.de

Stand: 1.1.1999

Seite 7