



Plattierte Flansche und Stutzen DIN 28038 mit glatter Dichtleiste sowie Nut und Feder

Werknorm
PF 28038

Nenn- weite DN	d1	Flansch			Plattierung				L	Schrauben		Gew. kg			
		h1	d2	d3	≈d9	h2	s1	s2		An zahl	d4				
1000	1000	50	1130	1080	1045	82	6,0	10,0	ca. 500	40	27	95,0			
		65	1150	1095	1060	105	8,0	14,0			30	148,0			
		70	1170	1105	1065	118	10,0	16,0			33	179,0			
1100	1100	50	1230	1180	1145	82	6,0	12,0		ca. 500	44	27	104,0		
		65	1250	1195	1160	105	8,0	14,0				30	156,0		
		70	1270	1205	1165	118	10,0	16,0				33	195,0		
1200	1200	55	1330	1280	1245	82	6,0	10,0			ca. 500	48	27	122,0	
		65	1350	1295	1260	105	8,0	16,0					30	171,0	
		75	1370	1305	1265	118	10,0	16,0					33	223,0	
1300	1300	55	1435	1385	1350	92	6,0	12,0				ca. 500	52	27	137,0
		70	1450	1395	1360	105	8,0	16,0						30	194,0
		75	1470	1405	1365	118	10,0	16,0						33	239,0
1400	1400	35	1515	1470	1440	67	6,0	10,0	ca. 500	56			23	83,0	
		60	1535	1485	1450	92	6,0	12,0					27	161,0	
		70	1550	1495	1460	105	8,0	14,0					30	210,0	
		75	1570	1505	1465	118	10,0	18,0					33	257,0	
1500	1500	40	1616	1570	1540	67	6,0	10,0		ca. 500			60	23	103,0
		60	1635	1585	1550	92	6,0	12,0						27	172,0
		70	1655	1600	1565	115	8,0	16,0			30	238,0			
		80	1675	1610	1570	128	11,0	20,0			33	310,0			
1600	1600	45	1715	1670	1640	67	6,0	10,0			ca. 500	64	23	120,0	
		60	1735	1685	1650	92	6,0	12,0					27	184,0	
		75	1755	1700	1665	115	8,0	16,0					30	272,0	
		80	1775	1710	1670	128	11,0	20,0					33	332,0	
1700	1700	45	1815	1770	1740	72	6,0	10,0	ca. 500			68	23	128,0	
		60	1835	1785	1755	92	6,0	12,0					27	194,0	
		75	1855	1800	1765	115	8,0	16,0					30	283,0	
		80	1875	1810	1770	128	11,0	20,0					33	351,0	
1800	1800	45	1915	1870	1840	72	6,0	10,0		ca. 500		72	23	136,0	
		65	1940	1890	1855	102	6,0	12,0					27	230,0	
		75	1955	1900	1865	115	8,0	16,0					30	300,0	
		80	1975	1910	1870	128	11,0	20,0					33	368,0	
1900	1900	45	2015	1970	1940	72	6,0	10,0			ca. 500	76	23	142,0	
		65	2040	1990	1955	102	6,0	12,0					27	242,0	
		80	2060	2005	1970	125	8,0	16,0					30	349,0	
		85	2080	2015	1975	138	11,0	20,0					33	433,0	
2000	2000	45	2115	2070	2040	72	6,0	10,0	ca. 500			80	23	149,0	
		65	2140	2090	2055	102	6,0	12,0					27	255,0	
		85	2160	2105	2070	125	8,0	16,0					30	382,0	
		95	2180	2115	2075	138	11,0	20,0					33	493,0	

Die vorgegebenen Rohrwanddicken s1 u. s2 sind Regelausführung. Dickere oder dünnere Wanddicke bei Anfragen angeben.



Erich Pokrandt GmbH
August-Bebel-Str. 3
67454 Hassloch / Pfalz

Telefon: 06324 / 923 923
Telefax: 06324 / 923 999
e-mail: info@pokrandt.de

Stand: 1.1.1999

Seite 16